Column & Fire Equipment Guidelines		Booth 4500
General booth guidelines can be found h	how/important-guidelines/display-guidelines-rule	NAMA Show
FEC FEC	,	4' 4601 FREIGHT DOOR 1'11"W X 32
FS (Fire Strobe): ACC exhibit hall are 20' height; <i>/</i> FE (Fire Extinguisher): Must remain visible, acces SP (Fire Speaker): 6"x6" & located at 9'9" height f and unobstructed FHC (Fire Hose Connection): Must remain visible, Door Release): Must not be blocked	ssible and unobstructed from the floor and shall be visible	Building Support Column Exhibitors are free to brand & build around columns, as long as fire equipment is clear and nothing is adhered to the column or physical building.
with measurements. This may vary slightly on	sible and accessible at all times and fire hoses ker at two different heights on a column	•

Anaheim Convention Center.

Freeman.

EVERY EFFORT HAS BEEN MADE TO ENSURE THE ACCURACY OF ALL INFORMATION CONTAINED ON THIS FLOORPLAN. HOWEVER, NO WARRANTIES, EITHER EXPRESSED OF IMPLIED, ARE MADE WITH RESPECT TO THIS FLOORPLAN. IF THE LOCATION OF BUILDING COLUMNS, UTILITIES OR OTHER ARCHITECTURAL COMPONENTS OF THE FACILITY IS A CONSIDERATION IN THE CONSTRUCTION OR USAGE OF AN EXHIBIT, IT IS THE SOLE RESPONSIBILITY OF THE EXHIBITOR TO PHYSICALLY INSPECT THE FACILITY TO VERIEV ALL DIMENSION AND LOCATIONS. ©COPYRIGHT 2007, FREEMAN, ALL RIGHTS RESERVED.